

參考文獻

- [1] P. R. Story, D. W. Galipeau, R. D. Mileham, A study of low-cost sensors for measuring low relative humidity, *Sens. Actuators B* 24-25 (1995) 681-685.
- [2] 劉明揚，大氣測計學，溼度 179 頁(2001)
- [3] 周華萍，1995，「生物感測器市場近況」，生物產業，第六卷，第一期。
- [4] Sauerbrey, G. Z., 1959, “Use of Quartz Crystal Vibrator for Weighting Thin Film on a Microbalance”, *Z. Phys*, Vol. 155, pp. 206-210.
- [5] 商周出版，呂宗昕「圖解奈米科技與光觸媒」。
- [6] C. Cantalini, M. Pelino, *J. Am. Ceram. Soc.* 75 (1992) 546–551.
- [7] H. Yagi, M. Nakata, *J. Ceram. Soc. Jpn.* 100 (1992) 152-286.
- [8] W.P. Tai, J.H. Oh, *Sens. Actuators B* 85 (2002) 154-287.
- [9] Q. Wan, Q.H. Li, Y.J. Chen, T.H.Wang, X.L. He, X.G. Gao, J.P. Li, 288 *Appl. Phys. Lett.* 84 (2004) 3085.
- [10] 中原大學碩士化學系學位論文，聚苯乙烯-蒙托土奈米複合材料之合成研究，柯子衡。
- [11] 蔡宗燕，化工資訊，“奈米級無機材料發展與應用” 12,2(1998)。
- [12] A.J.Cunningham, *Introduction to bioanalytical sensors*, New York: Wiley; (1998) p.307.

[13] Novel low humidity sensor made of TiO₂ nanowires/poly(2-acrylamido-2-methylpropane sulfonate) composite material film combined with quartz crystal microbalance.

[14] A low humidity sensor made of quartz crystal microbalance coated with multi-walled carbon nanotubes/Nafion composite material films.

[15] Quartz crystal microbalance coated with carbon nanotube films used as humidity sensor.

[16] Detection of humidity based on quartz crystal microbalance coated with ZnO nanostructure films.

[17] 吳朗，洪裕杰，2000，石英晶體微天平用於乙醇氣體感測器之設計與量測。

[18] Quartz crystal microbalance sensor based on nanostructured IrO₂

[19] O. J. Murphy, G. D. Hitchens, D. Hodko, E. T. Clarke, D. L. Miller, D. L. Parker, Method of manufacturing passive elements using conductive polypyrrole formulations, US Patent, (1999) 5855755.

[20] P. Poddar, J. L. Wilson, H. Srikanth, S. A. Morrison, E. E. Carpenter, Magnetic properties of conducting polymer doped with manganese-zinc ferrite nanoparticles, Nanotechnology 15 (2004) S570-S574.

[21] P. G. Su, Y. L. Sun, C. C. Lin, A low humidity sensor made of quartz microbalance coated with multi-walled carbon nanotubes/Nafion composite material films, Sens. Actuators B 115 (2006) 338-343.

[22] P. G. Su, Y. L. Sun, C. C. Lin, Novel low humidity sensor made of TiO₂ nanowires/poly(2-acrylamido-2-methylpropane sulfonate) composite material film combined with quartz crystal microbalance, Talanta 69 (2006) 946-951.

- [23] Q. Wan, Q. H. Li, Y. J. Chen, T. H. Wang, X. L. He, X. G. Gao, J. P. Li, Positive temperature coefficient resistance and humidity sensing properties of Cd-doped ZnO nanowires, *Appl. Phys. Lett.*, 84 (2004) 3085-3087.
- [24] R. Schaub, P. Thostrup, N. Lopez, E. Laegsgaard, I. Stensgaard, J. K. Nørskov, F. Besenbacher, Oxygen vacancies as active sites for water dissociation on Rutile TiO₂ (110), *Phys. Rev. Lett.*, 87 (2001) 266104-1-266104-4.
- [25] M. B. Kulwicki, Humidity sensors, *J. Am. Ceram. Soc.*, 74 (1991) 697-708.
- [26] L. X. Sun, T. Okada, Simultaneous determination of the concentration of methanol and relative humidity based on a single Nafion(Ag)-coated quartz crystal microbalance, *Anal. Chim. Acta* 421 (2000) 83-92.
- [27] Y. Okahata, M. Kawase, K. Niikura, F. Ohtake, H. Furusawa, Y. Ebara, Kinetic measurements of DNA hybridization on an oligonucleotide-immobilized 27-MHz quartz crystal microbalance, *Anal. Chem.* 70 (1998) 1288-1296.